



Select E-Line casters
are NSF listed.

E-1400/3400

*The Ultimate Value in
Multipurpose Casters & Wheels*



- Weight capacities up to 1,250 lbs
- Variety of the most popular 4", 5", 6" & 8" diameter x 2" tread width wheels
- Double ball raceways for smooth swiveling action
- 1/4" thick steel leg construction
- 5/8" nut & bolt kingpin
- RoHS compliant industrial zinc finish for corrosion resistance
- 1/2" hollow axle with grease zerk and lock nut
- 4 brake options: compatible on both swivel and rigid casters

Authorized Distributor / Distributeur Autorisé

Specifications

Wheel Dia.	Tread Width	Wheel Type	Load Capacity (Lbs)	Mount Height	Swivel Radius	Std. Bearing	Swivel Caster Part #	Rigid Caster Part #	Caster Bearing Options	Brake Options	Wheel Part # (Plain bore)	Wheel Bearing Options
4"	2"	Mold-on Rubber	400	5-5/8"	3-3/8"	Roller	ES4X2MOR	ER4X2MOR	(+) B	(+) WFB, TBK, CAMS, CAML	WH4X2MOR19	(+) B, R
		Thermo-Rubber (Flat)	350	5-5/8"	3-3/8"	Roller	ES4X2TPR	ER4X2TPR	(+) B, D		WH4X2TPR19	(+) B, D, R
		Thermo-Rubber (Donut)	350	5-5/8"	3-3/8"	Roller	ES4X2TPD	ER4X2TPD	(+) B, D		WH4X2TPD19	(+) B, D, R
		Thermo-Urethane (R/B)*	500	5-5/8"	3-3/8"	Roller	ES4X2TPU	ER4X2TPU	(+) B, D		WH4X2TPU19	(+) B, D, R
		Thermo-Urethane (M/G)*	500	5-5/8"	3-3/8"	Roller	ES4X2TUM	ER4X2TUM	(+) B, D		WH4X2TUM19	(+) B, D, R
		PolyKat™ Thermo-Urethane**	600	5-5/8"	3-3/8"	Prec.	ES4X2PKTP8	ER4X2PKTP8	N/A		WH4X2PKTP8	N/A
		Polypropylene HD	500	5-5/8"	3-3/8"	Roller	ES4X2POD	ER4X2POD	(+) B, D		WH4X2POD19	(+) B, D, R
		Phenolic	800	5-5/8"	3-3/8"	Roller	ES4X2PHN	ER4X2PHN	(+) B, D		WH4X2PHN19	(+) B, D, R
		Mold-on Poly	800	5-5/8"	3-3/8"	Roller	ES4X2MOP	ER4X2MOP	(+) B		WH4X2MOP19	(+) B, R
		Cast Iron	800	5-5/8"	3-3/8"	Roller	ES4X2CIR	ER4X2CIR	(+) B		WH4X2CIR19	(+) B, R
		No Wheel – Rig Only	1250	5-5/8"	3-3/8"	N/A	RIG4X2ES	RIG4X2ER	N/A		N/A	N/A
5"	2"	Mold-on Rubber	400	6-1/2"	4"	Roller	ES5X2MOR	ER5X2MOR	(+) B	(+) WFB, TBK, CAMS, CAML	WH5X2MOR19	(+) B, R
		Thermo-Rubber (Flat)	350	6-1/2"	4"	Roller	ES5X2TPR	ER5X2TPR	(+) B, D		WH5X2TPR19	(+) B, D, R
		Thermo-Rubber (Donut)	350	6-1/2"	4"	Roller	ES5X2TPD	ER5X2TPD	(+) B, D		WH5X2TPD19	(+) B, D, R
		Thermo-Urethane (R/B)*	600	6-1/2"	4"	Roller	ES5X2TPU	ER5X2TPU	(+) B, D		WH5X2TPU19	(+) B, D, R
		Thermo-Urethane (M/G)*	600	6-1/2"	4"	Roller	ES5X2TUM	ER5X2TUM	(+) B, D		WH5X2TUM19	(+) B, D, R
		PolyKat™ Thermo-Urethane**	800	6-1/2"	4"	Prec.	ES5X2PKTP8	ER5X2PKTP8	N/A		WH5X2PKTP8	N/A
		Polypropylene HD	600	6-1/2"	4"	Roller	ES5X2POD	ER5X2POD	(+) B, D		WH5X2POD19	(+) B, D, R
		Phenolic	1000	6-1/2"	4"	Roller	ES5X2PHN	ER5X2PHN	(+) B, D		WH5X2PHN19	(+) B, D, R
		Mold-on Poly	1100	6-1/2"	4"	Roller	ES5X2MOP	ER5X2MOP	(+) B		WH5X2MOP19	(+) B, R
		Cast Iron	1000	6-1/2"	4"	Roller	ES5X2CIR	ER5X2CIR	(+) B		WH5X2CIR19	(+) B, R
		No Wheel – Rig Only	1250	6-1/2"	4"	N/A	RIG5X2ES	RIG5X2ER	N/A		N/A	N/A
6"	2"	Mold-on Rubber	550	7-1/2"	4-3/4"	Roller	ES6X2MOR	ER6X2MOR	(+) B	(+) WFB, TBK, CAMS, CAML	WH6X2MOR19	(+) B, R
		Thermo-Rubber (Flat)	500	7-1/2"	4-3/4"	Roller	ES6X2TPR	ER6X2TPR	(+) B, D		WH6X2TPR19	(+) B, D, R
		Thermo-Rubber (Donut)	500	7-1/2"	4-3/4"	Roller	ES6X2TPD	ER6X2TPD	(+) B, D		WH6X2TPD19	(+) B, D, R
		Thermo-Urethane (R/B)*	720	7-1/2"	4-3/4"	Roller	ES6X2TPU	ER6X2TPU	(+) B, D		WH6X2TPU19	(+) B, D, R
		Thermo-Urethane (M/G)*	720	7-1/2"	4-3/4"	Roller	ES6X2TUM	ER6X2TUM	(+) B, D		WH6X2TUM19	(+) B, D, R
		PolyKat™ Thermo-Urethane**	1000	7-1/2"	4-3/4"	Prec.	ES6X2PKTP8	ER6X2PKTP8	N/A		WH6X2PKTP8	N/A
		Polypropylene HD	600	7-1/2"	4-3/4"	Roller	ES6X2POD	ER6X2POD	(+) B, D		WH6X2POD19	(+) B, D, R
		Phenolic	1200	7-1/2"	4-3/4"	Roller	ES6X2PHN	ER6X2PHN	(+) B, D		WH6X2PHN19	(+) B, D, R
		Mold-on Poly	1200	7-1/2"	4-3/4"	Roller	ES6X2MOP	ER6X2MOP	(+) B		WH6X2MOP19	(+) B, R
		Cast Iron	1200	7-1/2"	4-3/4"	Roller	ES6X2CIR	ER6X2CIR	(+) B		WH6X2CIR19	(+) B, R
		No Wheel – Rig Only	1250	7-1/2"	4-3/4"	N/A	RIG6X2ES	RIG6X2ER	N/A		N/A	N/A
8"	2"	Mold-on Rubber	600	9-1/2"	6-1/4"	Roller	ES8X2MOR	ER8X2MOR	(+) B	(+) WFB, TBK, CAMS, CAML	WH8X2MOR19	(+) B, R
		Thermo-Rubber (Flat)	600	9-1/2"	6-1/4"	Roller	ES8X2TPR	ER8X2TPR	(+) B, D		WH8X2TPR19	(+) B, D, R
		Thermo-Rubber (Donut)	600	9-1/2"	6-1/4"	Roller	ES8X2TPD	ER8X2TPD	(+) B, D		WH8X2TPD19	(+) B, D, R
		Thermo-Urethane (R/B)*	800	9-1/2"	6-1/4"	Roller	ES8X2TPU	ER8X2TPU	(+) B, D		WH8X2TPU19	(+) B, D, R
		Thermo-Urethane (M/G)*	800	9-1/2"	6-1/4"	Roller	ES8X2TUM	ER8X2TUM	(+) B, D		WH8X2TUM19	(+) B, D, R
		PolyKat™ Thermo-Urethane**	1200	9-1/2"	6-1/4"	Prec.	ES8X2PKTP8	ER8X2PKTP8	N/A		WH8X2PKTP8	N/A
		Polypropylene HD	900	9-1/2"	6-1/4"	Roller	ES8X2POD	ER8X2POD	(+) B, D		WH8X2POD19	(+) B, D, R
		Phenolic	1250	9-1/2"	6-1/4"	Roller	ES8X2PHN	ER8X2PHN	(+) B, D		WH8X2PHN19	(+) B, D, R
		Mold-on Poly	1250	9-1/2"	6-1/4"	Roller	ES8X2MOP	ER8X2MOP	(+) B		WH8X2MOP19	(+) B, R
		Cast Iron	1250	9-1/2"	6-1/4"	Roller	ES8X2CIR	ER8X2CIR	(+) B		WH8X2CIR19	(+) B, R
		No Wheel – Rig Only	1250	9-1/2"	6-1/4"	N/A	RIG8X2ES	RIG8X2ER	N/A		N/A	N/A

Wheel Choices



Bearing Choices




To change the standard roller bearing to an optional bearing in a caster, add B or D to the end of the part#. To order wheel only with bearing installed, replace 19 with bearing code R, B or D.


Brake Choices (All brakes work on swivel and rigid casters)



Sealed Raceway Choice



Top Plate Dimensions



Note: Swivel radius shown for standard models. Some brake models will have larger swivel radius.

** PolyKat™ wheel comes with Sealed Precision Ball Bearings, other bearing options not available. Cam Brakes are not an option with this wheel.